

## 'protecting your premises'

# from unwanted intruders with our Access Control Systems

Sales/Support - 1300NEVRAS

- ACCESS CONTROL SYSTEMS - BUILDING INTERCOMS - CCTV SURVEILLANCE SYSTEMS - SECURITY ALARM SYSTEMS - VIDEO DOOR PHONES -

## **Access Control System Reader**

**Product Code: NEV-ACS-READER-001** 

#### Features:

- Stand-alone unit
- Metal enclosure, anti-vandal with alarm function
- IP65 Rating for indoor and outdoor use in harsh environments
- Support Cards: 125Khz EM, 125KHz HID, 13.56MHz IC/CPU
- Reader can identify HID card format (but this is not with standard model)
- Output format: 26 bit default setting
- Suitable for storage areas, banks, prisons etc

### **Specifications:**

Operating Voltage: 12-18V AC/12-24V DC
Adjustable Door Relay Time: 0~99s

• Static Current: ≤35mA

Communication interface: Wiegand 26-37

Card Reading Range: 3-6cm
Reader Induction Time: ≤0.1s
Operating Temperature: -40°C ~ 60°C

Operating Humidity: 0-95%
Lock Output Load: 1A
Alarm Output Load: 3A

Antistatic: 15KV

Wiring Length: 90-100cm

Dimensions: L 135mm×W58mm×H 26mm



